



ATF DII

DESCRIPTION

Transmission fluid for automatic transmissions, power steering systems, torque converters and other applications requiring an ATF DII fluid.

APPLICATION

Bardahl ATF DII is particularly suitable for the transmissions of passenger cars, delivery vans, trucks and even some « off road » vehicles.

SPECIFICATIONS

This product offers the following performance level:

GM	DEXRON DII
MB	236.6/ 236.7
ZF	TE-ML 09/11A/14A
FORD	Mercon M2C-138CJ/ M2C-166H
MAN	339V1/ 339Z1
CAT	TO-2
ALLISON	C4
VOITH	G607/H55.6335

PROPERTIES

- ✓ Offers a good stability,
- ✓ Low pour point,
- ✓ Is highly resistant against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties,
- ✓ Red color.





TECHNICAL DATA

Density at 20°C	Kg/l	0,860
Viscosity at 40°C	mm ² /s	43,2
Viscosity at 100°C	mm ² /s	8,25
Viscosity Index		168
Flash point COC, °C	°C	198
Pour point, °C	°C	-45
T.B.N.	mgKOH/g	1,5
Sulphated Ash	%	0,18

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36231	12 x 1 L
36234	60 L
36237	205 L



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com