



TECHNICAL DATA SHEET
v012019

XTM 15W40

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter.

APPLICATION

Bardahl XTM 15w40 can be used all year long. It offers excellent cleaning properties and a very good protection against wear. Its thermal stability allows a prolonged use on road and highway.

SPECIFICATIONS

This product offers the following performance level:

API	SF/CF
MB	226.1
MIL	L-2104D / 46152B

PROPERTIES

- ✓ Avoids deposits on pistons,
- ✓ Provides excellent cleaning properties.

SADAPS BARDAHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com



TECHNICAL DATA SHEET
v012019

TECHNICAL DATA

Density at 20°C	Kg/l	0,869
Viscosity at -20°C	cP	4600
Viscosity at 40°C	mm2/s	98
Viscosity at 100°C	mm2/s	14
Viscosity Index		143
Flash point COC, °C	°C	208
Pour point, °C	°C	-26
Sulphated ash contents	%	1,2

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36261	12 x 1 L
36263	3 x 5 L
36268	20 L
36264	60 L
36267	205 L

SADAPS BARD AHL ADDITIVES & LUBRICANTS

ZI Tournai Ouest - 3, Rue du Mont des Carliers - B-7522 TOURNAI
Tél. : +32 69 590 360 - Fax : +32 69 590 361 - www.bardahlfrance.com