



XTG 75W90

DESCRIPTION

Synthetic oil with a high viscosity index, formulated to lubricate mechanical transmissions and differentials submitted to difficult operating conditions (heavy loads, high speed and temperature).

APPLICATION

Bardahl XTG 75w90 is particularly suitable for heavy loaded hypoid differentials. Provides an excellent stability at different temperatures.

SPECIFICATIONS

This product offers the following performance level:

| | |
|-----|----------------|
| API | GL5 |
| MIL | MIL-L-2105D |
| ZF | TE-ML 07A/ 17B |

PROPERTIES

- ✓ Offers a good resistance to high temperature,
- ✓ Provides very good extreme pressure (EP) properties,
- ✓ Has a low pour point,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties,
- ✓ Has a limited slip.





TECHNICAL DATA

| | | |
|---------------------|--------------------|-------|
| Density at 20°C | Kg/l | 0,873 |
| Viscosity at 40°C | mm ² /s | 87,9 |
| Viscosity at 100°C | mm ² /s | 15,20 |
| Viscosity index | | 184 |
| Flash point COC, °C | °C | 200 |
| Pour point, °C | °C | -42 |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

| | |
|-------|----------|
| 36381 | 12 x 1 L |
| 36383 | 3 x 5 L |
| 36388 | 20 L |
| 36384 | 60 L |
| 36387 | 205 L |



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com