



XTEC 0w30 V

DESCRIPTION

High performance 100% synthetic oil developed to limit fuel overconsumption. The additives are from the latest generations of technologies.

APPLICATION

Bardahl XTEC 0w30 V can be used in any petrol and diesel engine and is particularly suitable for Volvo vehicles.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A5/B5
API	SL
VOLVO	VCC 95200377

PROPERTIES

- ✓ Limits fuel overconsumption,
- ✓ Makes cold start easier, at very low temperatures (-40°C),
- ✓ Provides an excellent resistance against « shearing »,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties,
- ✓ High and stable viscosity index.





TECHNICAL DATA

Density at 15°C	Kg/l	0,843
Viscosity -35°C	mPa.s	5770
Viscosity 40°C	mm ² /s	53,10
Viscosity 100°C	mm ² /s	10,10
Viscosity index		181
Flash point COC, °C	°C	220
Pour point, °C	°C	-42
Alcalinity TBN	mgKOH/g	10,1
Sulfated ashes	%	1,09

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36973	3x5L
36977	205 L



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahloils.com