



INJECTOR CLEANER DIESEL BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS Ref.: 43040

Date of issue: 29-06-17 Revision date: 10-09-18 Supersedes: 29-06-17 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : INJECTOR CLEANER DIESEL BARD AHL
Product code : 43040 # 7304304R1
Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARRIERES, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

Supplier

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARRIERES, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674 Abu Dhabi	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

Signal word (CLP)

: Danger

Hazardous ingredients

: xylene (mixture); Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection, face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point.

EUH-statements

: EUH044 - Risk of explosion if heated under confinement.

Child-resistant fastening

: Applicable

Tactile warning

: Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	(EC-No.) 918-481-9 (REACH-no) 01-2119457273-39	40-60	Asp. Tox. 1, H304
xylene (mixture)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	15-30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
2-ethylhexyl nitrate	(CAS-No.) 27247-96-7 (EC-No.) 248-363-6 (REACH-no) 01-2119539586-27	5-15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 2, H411

INJECTOR CLEANER DIESEL BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	40-60	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified	(CAS-No.) 64742-94-5 (EC-No.) 265-198-5 (EC Index-No.) 649-424-00-3 (REACH-no) 01-2119463588-24	40-60	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-ethylhexan-1-ol	(CAS-No.) 104-76-7 (EC-No.) 203-234-3 (REACH-no) 01-2119487289-20	<3	Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
1,2,4-trimethylbenzene substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (FR)	(CAS-No.) 95-63-6 (EC-No.) 202-436-9 (EC Index-No.) 601-043-00-3 (REACH-no) 01-211947235-42	<1	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2	<0.5	Flam. Sol. 2, H228 Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3 (REACH-no) 01-2119471310-51	<0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Risk of explosion if heated under confinement.
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
---------------------------	---

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Recover the product with absorbent material.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Flammable liquid and vapour. Risk of explosion if heated under confinement.
Precautions for safe handling	: Do not eat, drink or smoke when using this product.
Hygiene measures	: Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation.
Storage conditions	: Store in a closed container. Keep out of frost.
Heat and ignition sources	: Keep away from naked flames/heat. Keep away from ignition sources.
Storage area	: Store in a dry place. Store in a well-ventilated place.
Special rules on packaging	: Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-ethylhexyl nitrate (27247-96-7)

EU	IOELV TWA (ppm)	1 ppm
----	-----------------	-------

2-ethylhexan-1-ol (104-76-7)

EU	Local name	2-ethylhexan-1-ol
EU	IOELV TWA (mg/m ³)	5,4 mg/m ³
EU	IOELV TWA (ppm)	1 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
France	VME (mg/m ³)	5,4 mg/m ³
France	VME (ppm)	1 ppm

1,2,4-trimethylbenzene (95-63-6)

EU	Local name	1,2,4-Trimethylbenzene
EU	IOELV TWA (mg/m ³)	100 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France	Local name	1,2,4-Triméthylbenzène

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1,2,4-trimethylbenzene (95-63-6)		
France	VME (mg/m ³)	100 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	250 mg/m ³
France	VLE (ppm)	50 ppm
France	Note (FR)	Valeurs réglementaires contraignantes
France	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)

naphthalene (91-20-3)		
EU	Local name	Naphthalene
EU	IOELV TWA (mg/m ³)	50 mg/m ³
EU	IOELV TWA (ppm)	10 ppm
EU	Notes	(Year of adoption 2010)
EU	Regulatory reference	COMMISSION DIRECTIVE 91/322/EEC; SCOEL Recommendations
Belgium	Local name	Naphtalène # Naftaleen
Belgium	Limit value (mg/m ³)	53 mg/m ³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m ³)	80 mg/m ³
Belgium	Short time value (ppm)	15 ppm
Belgium	Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
France	Local name	Naphtalène
France	VME (mg/m ³)	50 mg/m ³
France	VME (ppm)	10 ppm
France	Note (FR)	Valeurs recommandées/admises; substance classée cancérogène de catégorie 2
France	Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)

xylene (mixture) (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Xylène, isomères mixtes, purs # Xyleen, mengsel van isomeren, zuiver
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (mixture) (1330-20-7)		
Belgium	Short time value (mg/m ³)	442 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m ³)	221 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
France	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)

Ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m ³)	442 mg/m ³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m ³)	884 mg/m ³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
France	Local name	Ethylbenzène
France	VME (mg/m ³)	88,4 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	402 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
France	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)

Toluene (108-88-3)		
EU	Local name	Toluene
EU	IOELV TWA (mg/m ³)	192 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	384 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium	Local name	Toluène # Tolueen

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Toluene (108-88-3)		
Belgium	Limit value (mg/m ³)	77 mg/m ³
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m ³)	384 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
France	Local name	Toluène
France	VME (mg/m ³)	76,8 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	384 mg/m ³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée
France	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)

8.2. Exposure controls

Hand protection:
Gloves. EN 374
Eye protection:
Safety glasses. EN 166
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
Good ventilation of the workplace required. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear.
Colour	: dark orange.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 40 °C

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,83 g/cm ³ (20°C)
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: < 20,5 mm ² /s (40°C)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified (64742-94-5)

LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat (mg/l)	> 590 mg/m ³

2-ethylhexan-1-ol (104-76-7)

LD50 oral rat	> 3290 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

1,2,4-trimethylbenzene (95-63-6)

LC50 inhalation rat (mg/l)	18000 mg/m ³
----------------------------	-------------------------

naphthalene (91-20-3)

LD50 oral	490 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LD50 dermal	> 2500 mg/kg
LC50 inhalation rat (mg/l)	> 340 mg/m ³

xylene (mixture) (1330-20-7)

LD50 oral rat	2000 mg/kg
---------------	------------

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 dermal	1100 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1,5 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	11 mg/l/4h

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	28,1 mg/l/4h

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4951 mg/m ³ 4 hours

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs (central nervous system, kidneys, liver) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

INJECTOR CLEANER DIESEL BARDAHL

Viscosity, kinematic	< 20,5 mm ² /s (40°C)
----------------------	----------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.

2-ethylhexyl nitrate (27247-96-7)

LC50 fish 1	28,2 mg/l (Pimephales promelas, 4DY)
LC50 fish 2	17,1 mg/l (Ide mélanote (Leuciscus idus),4DY)
EC50 other aquatic organisms 1	> 12,6 mg/l (Cladocère, 2DY)

Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified (64742-94-5)

LC50 fish 1	2 - 5 mg/l
EC50 Daphnia 1	3 - 10 mg/l
EC50 72h algae (1)	< 10 mg/l

2-ethylhexan-1-ol (104-76-7)

LC50 fish 1	28,2 mg/l (Pimephales promelas, 4DY)
EC50 Daphnia 1	39 mg/l (Daphnia magma)
EC50 72h algae (1)	11,5 mg/l (Desmodesmus subspicatus)

1,2,4-trimethylbenzene (95-63-6)

LC50 fish 1	7,72 mg/l 4 days
EC50 other aquatic organisms 1	3,6 mg/l

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

naphthalene (91-20-3)	
LC50 fish 2	>= 2350 µg/l 48 hours
EC50 Daphnia 1	1,96 mg/l 48 hours

xylene (mixture) (1330-20-7)	
LC50 fish 1	2 - 11 mg/l
LC50 fish 2	13,5 mg/l
LC50 other aquatic organisms 1	21 mg/l
EC50 Daphnia 1	1 - 5 mg/l
EC50 72h algae (1)	3 - 5 mg/l

Ethylbenzene (100-41-4)	
LC50 fish 1	12,1 mg/l
EC50 Daphnia 1	1,8 - 2,4 mg/l
EC50 72h algae (1)	438 mg/l

Toluene (108-88-3)	
LC50 fish 1	5,5 mg/l
EC50 Daphnia 1	3,78 mg/l
EC50 72h algae (1)	10 mg/l
LOEC (chronic)	2,77 mg/l 40 days onchorhynchus mykiss
NOEC chronic fish	1,39 mg/l 40 days onchorhynchus mykiss
NOEC chronic crustacea	10 mg/l

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	> 1000 mg/l
EC50 72h algae (1)	> 1000 mg/l

12.2. Persistence and degradability

xylene (mixture) (1330-20-7)	
Persistence and degradability	Readily biodegradable.

Ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Biodegradation	80 % 28 days

12.3. Bioaccumulative potential

2-ethylhexyl nitrate (27247-96-7)	
Log Kow	5,24

1,2,4-trimethylbenzene (95-63-6)	
Log Kow	3,63

INJECTOR CLEANER DIESEL BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (mixture) (1330-20-7)	
Log Pow	2,77 - 3,15
Bioaccumulative potential	not bioaccumulable.

Ethylbenzene (100-41-4)	
Log Pow	3,5

Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Pow	2,65
Bioaccumulative potential	not bioaccumulable.

12.4. Mobility in soil

2-ethylhexyl nitrate (27247-96-7)	
Mobility in soil	(terre-3,75)

xylene (mixture) (1330-20-7)	
Ecology - soil	insoluble in water. Floats on water.

Ethylbenzene (100-41-4)	
Ecology - soil	insoluble in water.

Toluene (108-88-3)	
Surface tension	0,0242 mN/m 20°C

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Product/Packaging disposal recommendations	: Collect all waste in suitable and labelled containers and dispose according to local legislation.
Additional information	: Empty the packaging completely prior to disposal. Do not re-use empty containers.
Ecology - waste materials	: Do not discharge the product into the environment.

SECTION 14: Transport information





In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	RID
14.1. UN number			
1993	1993	1993	1993
14.2. UN proper shipping name			
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.
Transport document description			
UN 1993 FLAMMABLE LIQUID, N.O.S. (CONTAINS ; xylene (mixture) ; Ethylbenzene), 3, III, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III	UN 1993 Flammable liquid, n.o.s., 3, III	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

INJECTOR CLEANER DIESEL BARDAHL


Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)			
3	3	3	3
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 

Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 223, 274, 955
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3L

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 274, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

Detergent Regulation : Labelling of contents:	
Component	%
aliphatic hydrocarbons	>=30%
aromatic hydrocarbons	15-30%

Directive 2012/18/EU (SEVESO III)

15.1.2. National regulations

France

Occupational diseases : RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant
RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Germany

Reference to AwSV : Water hazard class (WGK) 3, severe hazard to water (Classification according to AwSV, Annex 1)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified is listed
SZW-lijst van mutagene stoffen : Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : xylene (mixture), Toluene are listed

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226;H304;H315;H319;H335;H373;H412>; Emergency management guidelines for the storage of flammable liquids must be followed

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

INJECTOR CLEANER DIESEL BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EUH044	Risk of explosion if heated under confinement.
--------	--

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product